





SPY 66 CLIP TW 96518 W-W

24622 9010 W-W

BESCHIKBAAR IN
ZWART-ZWART 24622 9010 B-B
WIT-WIT 24622 9010 W-W



 [Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw, Plafond Opbouw
ZAAGMAAT/OPENING (MM)	rond - 51
INBOUWDIEPTE (MM)	40
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.6
RICHTBAARHEID	0° tot 90° zwenkbaar, 355° roteerbaar
INFO	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

Elektrische info

KLASSE	III
DIM TYPE	afhankelijk van de te kiezen externe voeding
ENERGIE KLASSE	E
CERTIFICATEN	CB, ENEC

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30-15 WAARDEN	Rf: 89 / Rg: 100
SDCM	SDCM2
RISK-GROEP	RG1
LM80	L90B10 > 50000
LED TECHNIEK (LICHTBRON)	1087lm // 9W // 121lm/W
LED TECHNIEK (TOESTEL)	776lm // 10W // 75lm/W

Benodigdheden

SPY 66 TUBE
 LED POWER SUPPLY 500mA-DC TW

Opties

MOUNTING KIT FLUSH SPY

SPY 66 CLIP TW 96518 W-W

















24622 9010 W-W

Accessoires

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

Voor gedetailleerde montage gegevens, consulteer de handleiding: [24622_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT FLUSH SPY	Required
 Plasterboard	 MOUNTING KIT FLUSH SPY	Required
 Stucanet	 MOUNTING KIT FLUSH SPY	Required
 Wood	-	
 Concrete	-	
 Concrete + plaster	 MOUNTING KIT FLUSH SPY	Required
 Lintel + plaster	 MOUNTING KIT FLUSH SPY	Required
 Hollow-core slab	-	
 Hollow-core slab + plaster	 MOUNTING KIT FLUSH SPY	Required
 Stretched ceiling	-	


SPY 66 CLIP TW 96518 W-W

24622 9010 W-W

VERVOLLEDIG UW SPECIFICATIE

LED voedingen


#



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

Montage kit




414 90 01 MOUNTING KIT FLUSH SPY


SPY 66 CLIP TW 96518 W-W

24622 9010 W-W


Light veranderende onderdelen




24611 0150 B HONEYCOMB 57 SINGLE USE B




24611 0160 GLASS SBL 57




24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57



24611 0200 SPREAD LENS 57




24611 0210 B HONEYCOMB 57 DOUBLE USE B

SPY 66 CLIP TW 96518 W-W

24622 9010 W-W

Maak je product af



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Vervangbare reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°

Notes: