


2632

Design By Arik Levy

Ceiling light with basic lines and cubic volumes that form sculptures integrated into the architecture.

Model Sheet



Finish


- 21 Black Grey
NCS S 7000-N
- 15 Grey L2
NCS S 2500-N

LED temperature color 3000 K / 3500 K / 4000 K

Dimming CASAMBI / 1-10V / DALI




Installation type Surface Canopy

Materials Body: Aluminum
Diffuser: Polycarbonate
Profile: Aluminum

LED  CRI>90
3000 K / 3500 K / 4000 K

Driver Constant Voltage 110~240 V V
50~60 Hz HZ

Remarks Main input by the biggest box

  **Dimmable** **LED**
IP20 **Bi-volt** **50-60Hz** 


Application Ceiling Lamps

Packaging 1 Box
0,24 m x 0,38 m x 0,38 m
Gross weighth 3,3
Net weighth 2,8
Vol. 0.0346

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency 68.54 lm/W
Coordinate System CG
Total Flux 1507.91 lm
Maximum Value 660.02 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com